

Model NO. /Decription	CARRIER BOX	
	General specification	
	TPO injection moulding front cowl and rear	
Body	body	l.
Chasis	Electrophoresis Chasis	Ļ
Motor	4KW AC Motor	Ļ
Controller	400AMP	Ļ
Suspension	Independent suspension with four arms	ł
Accelerator	Adjustable 0-5k resistor accelerator continuously variable speed system	
Brake	Mechnical brake	
Steering	Left hand driving	
Sieeling	Self compensating"Rack & Pinion" steering	ł
wheels	10 inch Aluminum wheels	
Tires	205/50-10' tires	
Windshield	foldable windshield	
Dashboard	4 bottle holders	
Floor	Resin synthesis and Anti-slid rubber mat	
Roof	TPO Injection moulding	
Lighting system	12V, headlight (with hight/low beam), front turning light, LED taillights (includes brake lights and turning light),	
Voltage reducer	48V to 12V voltage reducer for all accessories	l
Charger	25A On-board Charger	
Battery	Lithium battery 110Ah	
Rear view mirrors	Included	
	Performance	
Passenger capacity	2	
Load range(km)	>80	
Max. speed(Km/h)	30	
Max. movement after brake(m)	<3.5	
Minimum turning radius (m)	3,1	
Max. climbing ability (loaded)	25%	
	Dimensions	
Overall dimention(mm)	2380x1400x1830	
Curb weight(Kg)	391	
Max total mass(Kg)	531	
Wheel base(mm)	1650	
Front wheel Tread(mm)	880	İ
INOX BOX	80 X 110 X 100 cm	i
Rear wheel Tread(mm)	980	*A
,		



PHOTOS





*Also available with ThermoBox or ThermoBox + Motor

